

Mody

Velocità Giri/min ¹	Speed R.p.m.	Geschw. U/m in ¹	Velocidad R.p.m.	Vitesse Tours/min ¹
Carico statico max	Max static load	Max statisch e Achslast	Carga estatica max	Charge statique ma x

Differenza di tiro in kg con rendimento del vano = 0,8
 Out of balance load in kg with shaft efficiency = 0,8
 Zugkräfte in kg mit Schachtwirkungsrad = 0,8
 Carga descompensada en kg con rendimiento del hueco = 0,8
 Force de traction en kg avec rendement de la gaine = 0,8

VF

1500 rpm
2250kg

kW
SYNC

kW	kW	kW	kW	kW	kW	kW	kW	kW	kW				m/s	ratio	Ø mm
2,2	2,6	3,2	3,5	4,0	4,4	5,1	5,6	5,9	6,5						
209	244	300	335	384	418	493							0.68	1/37	320
186	217	267	298	341	372	425							0.76	1/37	360
167	195	240	268	307	335	395							0.85	1/37	400
139	163	200	223	256	279	319							1.02	1/37	480
146	171	206	225	259	286	333	366						1.07	2/47	320
129	150	185	206	236	257	294							1.10	1/37	520
120	139	171	191	219	239	275							1.19	1/37	560
130	152	183	200	230	254	296	326						1.20	2/47	360
112	130	160	179	205	223	263							1.27	1/37	600
117	137	165	180	207	228	266	293						1.34	2/47	400
98	114	137	150	173	190	222	244						1.60	2/47	480
90	105	127	139	159	176	205	225						1.74	2/47	520
88	103	126	141	161	176	202	223	235	258				1.84	3/41	320
84	98	117	129	148	163	190	209						1.87	2/47	560
78	91	110	120	138	152	177	195						2,01	2/47	600
78	91	112	125	143	157	180	198	209	227				2,07	3/41	360
70	82	101	113	129	141	162	178	189	207				2.30	3/41	400
59	68	84	94	108	117	135	149	158	170				2.76	3/41	480
54	63	78	87	99	108	125	137	145	157				2.99	3/41	520
50	59	72	80	92	101	116	127	135	146				3.22	3/41	560
47	55	67	75	86	94	108	119	126	136				3.45	3/41	600